

POLYOLEFIN

Polyolefin structure pouch available in two colors, white or blue, an outstanding solution for packaging fragile or valuable products with a focus on cosmetic protection during transportation or storage. Prefix: EXT-W5.

STANDARDS

This product complies with Type I requirements (normal strength resistance), Type II (3, 4 and 6 mil) (high strength resistance), class 2 (for use in contact with food), grade B (medium slip), finish 1 (untreated) of federal specification A-A-3174. Complies with the following FDA regulations: 21 CFR 175.320, 21 CFR 177.1010, 21 CFR 177.1520, 21 CFR 177.1350, 21 CFR 178.2010, 21 CFR 178.3295, 21 CFR 178.3570, 21 CFR 179.45


SPECIFICATIONS

Physical Properties	Typical Values	Testing Standard
Thickness	6.4 mils	
Tensile Strength	8 kg / inch (17.6 lb / in)	ASTM D5034-95 (Grab Test)
Elongation	60%	ASTM D5034-95 (Grab Test)

Heat Seal Conditions

Temperature	250 - 375 °F (120 - 180 °C)
Time	0.5 - 3.5 seconds
Pressure	30 - 70 psi

FITMENTS




STYLES



For products that require packaging which provides cosmetic protection

Nonwoven fabric recommended for those products which are especially sensitive to scratching or cosmetic damage. Available in various gauges for greater protection.

Front of the bag



Back of the bag



Before using this product, we recommend that user conduct a thorough evaluation of this product through the testing and use of a statistically significant number of samples of said product. Furthermore, it is the final user's sole responsibility to verify the validity and appropriateness of the information contained herein.